

Thank you for purchasing your new SKIMZ Recirculating Biopellet Reactor that provides optimum performance with maximum safety and reliability.

| M | odel | Reactor Pump | Body Diameter (mm) | Biopellet Media (ml) | Phosphate/Carbon Media (ml) | For Aquarium | Code |
|---|------|--------------|-----------------------|-------------------------|--------------------------------|---------------|---------|
| R | R97 | QP1.2 | 90 | up to 700 | up to 600 | up to 700 L | 8402-00 |
| R | R117 | QP2.0 | 110 | up to 1,200 | up to 1,000 | up to 1,200 L | 8403-00 |
| R | R157 | QP4.0 | 150 | up to 2,000 | up to 1,800 | up to 2,000 L | 8404-00 |

MAINTENANCE

It is recommended to clean the reactor when new media is replaced. The recirculation pump and water outlet control valve should be cleaned to ensure that it does not blocked with debris from the tank or calcium deposits.

Every three months:

Clean the recirculation pump and inspect impeller for potential wear.

Every six months:

- 1. Remove the media, rinse it under running water.
- 2. Clean the whole reactor to remove salt creep.
- 3. Slightly lubricate the O-rings with silicone grease.

WARRANTY POLICY

AAP Marketing Pte Ltd (Company) warrants this product to the original purchaser against defective material and workmanship that occurs during normal use of the body for two (2) years and one (1) year warranty on the pump. Company will, at Company's option, either repair or replace without charge.

PRODUCTS COVERED BY WARRANTY

All Skimz equipment is covered by warranty from the date of purchase.

To be effective, register your product at: **www.skimz.sg**, product warranty within 14 days of the product's purchase date.

Exclusions:

Damage resulting from accident, misuse, lack of reasonable care, subjecting the product to abnormal working conditions or any other failure not resulting from defects in materials or workmanship.

Damage caused by tampering, modification or attempted repair by anyone other than the Company.

Transfer of product to someone other than the original purchaser.

Bring the product to your nearest Skimz dealer or ship the product, together with a copy of the purchase receipt or other evidence of purchase to:

AAP Marketing Pte Ltd

5 Ang Mo Kio Industrial Park 2A #04-30 AMK Tech II Singapore 567760


You must pay any postage, shipping charges, insurance costs and other expenses to return the product to AAP. However, if the necessary repairs are covered by the warranty, Company will pay the return shipping charges.

QUICK INSTALLATION GUIDE



RR97 • RR117 • RR157

SKIMZ



A. Thumbscrew

B. Lid

C. Water outlet tube

D. Water outlet valve (Effluent)

E. Dispersion cone

F. Reactor pump


G. Port Plug (Quick air release)

H. Plug holder

I. DC pump controller


J. Sponge (when reactor is utilize as fluidized reactor)

K. DC power supply




STEP 1

- 1. Open the lid by removing the thumbscrews anticlockwise.
- 2. Remove Port Plug from the plug holder than insert Port Plug into the centre flow tube thereafter pour media into the reactor chamber.
- 3. Replace O-Ring. In event that O-Ring is unable to fit, it's desirable to circumferentially stretched 2-5%. By stretching O-Ring, we ensure that O-Ring will not fall out or twist.
- 4. Replace Port Plug in the plug holder. Reattach the lid and tighten all screws.




STEP 2

- 1. Fully open the Water Outlet Valve and place the reactor in the sump tank.
- 2. Submerge the Water Outlet Tube in the sump tank.
- 3. Wait for 3-5 mins to let the reactor fill itself with water.



STEP 3


- 1. Connect the pump and the DC power supply to the DC pump controller than plug in the DC power supply to the wall socket or gang socket.
- 2. Turn on the reactor pump and let it prime. The average prime time is 3-5 mins.
- 3. If you experience the reactor cannot complete priming due to too much air trapped in the pump chamber. Remove Port Plug and add about 500ml of water to assist the priming process. Replace the Port Plug instantly after adding water.
- 4. Regulate the flow rate until all the media is tumbling, so that it will keep the media free of biofilm. Adjust the water outlet of your effluent according to your bio-load.



STEP 4

When using this equipment as Fluidized Reactor.

- 1. Insert the provided sponge at bottom and top of the reacting chamber
- 2. This equipment can be used with Phosphate media or activated carbon.



STEP 5

When using this equipment as Fluidized Reactor.

- 1. Carry out STEP 2 for placement of Reactor.
- 2. Carry out STEP 3 for priming processes.
- 3. Adjust the flow rate until the media starts to fluidize.
- 4. When fluidizing media, we suggest that the flow must not be too strong to avoid media disintegration. A general guide is to provide sufficient flow such that the surface of the media are moving gently.

skimz.sg | info@skimz.sg